

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Express Mail No.: EL627430172US

In re Application of: TALVITIE et al.

FILING DATE: Herewith

ART UNIT:

TITLE: A SYSTEM FOR MEASURING A RADIO FREQUENCY SIGNAL IN A
WIRELESS STATION AND A WIRING BOARD SWITCH

ATTORNEY DOCKET NO.: 460-010212-US(PAR)

The Commissioner of Patents and Trademarks
Washington, D.C. 20231

PRELIMINARY AMENDMENT

Dear Sir:

Please amend the above-identified, enclosed patent application as follows:

IN THE CLAIMS

Please amend claims 3, 4, 6, 8, 9, 13, 14, 15, 17 and 18 as rewritten below:

3. A system according to Claim 1, in which the wireless station (1) also comprises at least a shell (16), **characterized** in that a testing aperture (17) is provided in said shell (16) essentially at least partly at the location of the switching aperture (4), through which testing aperture (17) and switching aperture (4) said switching means (3, 22) is arranged to be switched to the second position.
4. A system according to claim 1, **characterized** in that said switching means (3, 22) is arranged to be switched to the second position with the measuring head (6).
6. A system according to claim 1, whereby the wireless station (1) comprises at least one grounding connection (13) on the wiring board (2), **characterized** in that the system also comprises at least a testing card (9) and means (19) for coupling the testing card to the wireless station, which testing card (9) is coupled to the testing apparatus (7) with said means (12) for transmitting electrical signals, which

testing card (9) is arranged to be placed in said means (19) for coupling the testing card to the wireless station, that the measuring head (6) is installed in a testing aperture (4) formed in the wiring board (2) of the wireless station (1), that said testing card (9) comprises at least mode switching means (15), one grounding connection (10) and a measuring connection (11), and the mode switching means (15) are arranged to push said switching means (3, 22) to the second position by means of the measuring head (6), whereupon the grounding means (10) are coupled to an electrically conductive connection in the grounding connection (13), the measuring head (6) is coupled to an electrically conductive connection in said switching means (3, 22) and the measuring head (6) is coupled to an electrically conductive connection in the measuring connection (11), whereupon the radio frequency signal is directed between the radio part (8) of the wireless station (1) and the testing apparatus (7) via said switching means (3, 22), measuring head (6) and testing card (9).

8. A system according to claim 1, whereby the wireless station (1) comprises at least one grounding connection (13) on the wiring board (2), **characterized** in that the system also comprises at least a testing card (9) and means (19) for coupling the testing card to the wireless station, the testing card (9) is coupled to the testing apparatus (7) with said means (12) for transmitting electrical signals, the testing card (9) is arranged to be placed in said means (19) for coupling the testing card to the wireless station for carrying out the measurement, that said testing card (9) comprises at least one measuring head (6) and a grounding connection (10), and the measuring head (6) is arranged to switch said switching means (3, 22) to the second position, whereupon the grounding means (10) are coupled to an electrically conductive connection in the grounding connection (13) and the measuring head (6) is connected to an electrically conductive connection in said switching means (3, 22), whereupon the radio frequency signal is directed between the radio part (8) of the wireless station (1) and the testing apparatus (7) via said switching means (3, 22), measuring head (6) and the testing card (9).
9. A system according to claim 6, whereby the wireless station (1) comprises at least one SIM card (18), **characterized** in that the above mentioned means (19) for coupling the testing card to the wireless station comprise at least one SIM card slot (19), into which the SIM card (18) is arranged to be placed, and the above mentioned testing card (9) is arranged to be placed instead of the SIM card (18) in the SIM card slot (19).

13. A method according to Claim 11, whereby the wireless station (1) also comprises at least a shell (16), **characterized** in that a testing aperture (17) is formed in said shell (16) essentially at least partly at the location of the switching aperture (4), through which testing aperture (17) and switching aperture (4) said switching means (3, 22) is switched to the second position.
14. A method according to claim 11, **characterized** in that for carrying out the measurement, said switching means is switched to the second position with the measuring head (6).
15. A method according to claim 11, whereby the wireless station (1) comprises at least one grounding connection (13) on the wiring board (2), **characterized** in that the testing equipment (6, 7, 12) mentioned above also comprises at least a testing card (9) and means (19) for coupling the testing card to the wireless station, the testing card (9) is coupled to the testing apparatus (7) with said means (12) for transmitting electrical signals, and the testing card (9) is placed in said means (19) for coupling the testing card to the wireless station for carrying out the measurement, that said testing card (9) comprises at least mode switching means (15), one grounding connection (10) and a measuring connection (11), and when the testing card (9) is installed, the mode switching means (15) push said switching means (3, 22) to the second position by means of the measuring head (6) in the switching aperture (4) in the wiring board (2) of the wireless station (1), the grounding means (10) are coupled to an electrically conductive connection in the grounding connection (13), the measuring head (6) is coupled to an electrically conductive connection in said switching means (3, 22) and the measuring head (6) is coupled to an electrically conductive connection in the measuring connection (11), whereupon the radio frequency signal is directed between the radio part (8) of the wireless station (1) and the testing apparatus (7) via the measuring head (6) and testing card (9).
17. A method according to claim 11, whereby the wireless station (1) comprises at least a SIM card (18), a SIM card slot (19) in which the SIM card (18) is placed, and at least one grounding connection (13) on the wiring board (2), **characterized** in that the testing equipment (6, 7, 12) mentioned above also comprises at least a testing card (9) and means (19) for coupling the testing card to the wireless station, which testing card (9) is coupled to the testing apparatus (7) with said means (12) for transmitting electrical signals, which testing card (9) is placed in said means (19) for coupling the testing card to the wireless station for carrying


out the measurement, that said testing card (9) comprises at least one measuring head (6) and a grounding connection (10), and when the testing card (9) is installed, the measuring head (6) switches said switching means (3, 22) to the second position, the grounding means (10) are coupled to an electrically conductive connection in the grounding connection (13), and the measuring head (6) is coupled to an electrically conductive connection in said switching means (3, 22), whereupon the radio frequency signal is directed between the radio part (8) of the wireless station (1) and the testing apparatus (7) via the measuring head (6) and testing card (9).

18. A method according to claim 15, whereby the wireless station (1) comprises at least one SIM card (18), **characterized** in that the above mentioned means (19) for coupling the testing card to the wireless station comprise at least one SIM card slot (19), in which the SIM card (18) is placed, whereupon the above mentioned testing card (9) is placed instead of the SIM card (18) in the SIM card slot (19) for carrying out the measurements.

REMARKS

In accordance with 37 C.F.R. §1.121 (as amended on 11/7/2000) the rewritten claim(s) above are shown on separate page(s) marked up to show all the changes relative to the previous version of that section.

Respectfully submitted,



Clarence A. Green, Reg. No.: 24,622

Perman & Green, LLP

425 Post Road

Fairfield, CT 06430

(203) 259-1800

Customer No.: 2512



Date

Application entitled: A SYSTEM FOR MEASURING A RADIO FREQUENCY SIGNAL IN A WIRELESS STATION AND A WIRING BOARD SWITCH

MARKED UP CLAIM(S)

3. A system according to Claim 1-~~or~~2, in which the wireless station (1) also comprises at least a shell (16), **characterized** in that a testing aperture (17) is provided in said shell (16) essentially at least partly at the location of the switching aperture (4), through which testing aperture (17) and switching aperture (4) said switching means (3, 22) is arranged to be switched to the second position.
4. A system according to ~~any one of the claims 1, 2 or 3~~**claim 1**, **characterized** in that said switching means (3, 22) is arranged to be switched to the second position with the measuring head (6).
6. A system according to ~~any one of the claims 1 to 4~~**claim 1**, whereby the wireless station (1) comprises at least one grounding connection (13) on the wiring board (2), **characterized** in that the system also comprises at least a testing card (9) and means (19) for coupling the testing card to the wireless station, which testing card (9) is coupled to the testing apparatus (7) with said means (12) for transmitting electrical signals, which testing card (9) is arranged to be placed in said means (19) for coupling the testing card to the wireless station, that the measuring head (6) is installed in a testing aperture (4) formed in the wiring board (2) of the wireless station (1), that said testing card (9) comprises at least mode switching means (15), one grounding connection (10) and a measuring connection (11), and the mode switching means (15) are arranged to push said switching means (3, 22) to the second position by means of the measuring head (6), whereupon the grounding means (10) are coupled to an electrically conductive connection in the grounding connection (13), the measuring head (6) is coupled to an electrically conductive connection in said switching means (3, 22) and the measuring head (6) is coupled to an electrically conductive connection in the measuring connection (11), whereupon the radio frequency signal is directed between the radio part (8) of the wireless station (1) and the testing apparatus (7) via said switching means (3, 22), measuring head (6) and testing card (9).

8. A system according to ~~any one of the claims 1 to 4~~claim 1, whereby the wireless station (1) comprises at least one grounding connection (13) on the wiring board (2), **characterized** in that the system also comprises at least a testing card (9) and means (19) for coupling the testing card to the wireless station, the testing card (9) is coupled to the testing apparatus (7) with said means (12) for transmitting electrical signals, the testing card (9) is arranged to be placed in said means (19) for coupling the testing card to the wireless station for carrying out the measurement, that said testing card (9) comprises at least one measuring head (6) and a grounding connection (10), and the measuring head (6) is arranged to switch said switching means (3, 22) to the second position, whereupon the grounding means (10) are coupled to an electrically conductive connection in the grounding connection (13) and the measuring head (6) is connected to an electrically conductive connection in said switching means (3, 22), whereupon the radio frequency signal is directed between the radio part (8) of the wireless station (1) and the testing apparatus (7) via said switching means (3, 22), measuring head (6) and the testing card (9).
9. A system according to ~~any one of the claims 6, 7 or 8~~claim 6, whereby the wireless station (1) comprises at least one SIM card (18), **characterized** in that the above mentioned means (19) for coupling the testing card to the wireless station comprise at least one SIM card slot (19), into which the SIM card (18) is arranged to be placed, and the above mentioned testing card (9) is arranged to be placed instead of the SIM card (18) in the SIM card slot (19).
13. A method according to ~~Claim 11 or 12~~, whereby the wireless station (1) also comprises at least a shell (16), **characterized** in that a testing aperture (17) is formed in said shell (16) essentially at least partly at the location of the switching aperture (4), through which testing aperture (17) and switching aperture (4) said switching means (3, 22) is switched to the second position.
14. A method according to ~~any one of the claims 11, 12 or 13~~claim 11, **characterized** in that for carrying out the measurement, said switching means is switched to the second position with the measuring head (6).
15. A method according to ~~any one of the claims 11 to 14~~claim 11, whereby the wireless station (1) comprises at least one grounding connection (13) on the wiring board (2), **characterized** in that the testing equipment (6, 7, 12) mentioned above also comprises at least a testing card (9) and means (19) for

coupling the testing card to the wireless station, the testing card (9) is coupled to the testing apparatus (7) with said means (12) for transmitting electrical signals, and the testing card (9) is placed in said means (19) for coupling the testing card to the wireless station for carrying out the measurement, that said testing card (9) comprises at least mode switching means (15), one grounding connection (10) and a measuring connection (11), and when the testing card (9) is installed, the mode switching means (15) push said switching means (3, 22) to the second position by means of the measuring head (6) in the switching aperture (4) in the wiring board (2) of the wireless station (1), the grounding means (10) are coupled to an electrically conductive connection in the grounding connection (13), the measuring head (6) is coupled to an electrically conductive connection in said switching means (3, 22) and the measuring head (6) is coupled to an electrically conductive connection in the measuring connection (11), whereupon the radio frequency signal is directed between the radio part (8) of the wireless station (1) and the testing apparatus (7) via the measuring head (6) and testing card (9).

17. A method according to ~~any one of the claims 11 to 14~~ claim 11, whereby the wireless station (1) comprises at least a SIM card (18), a SIM card slot (19) in which the SIM card (18) is placed, and at least one grounding connection (13) on the wiring board (2), **characterized** in that the testing equipment (6, 7, 12) mentioned above also comprises at least a testing card (9) and means (19) for coupling the testing card to the wireless station, which testing card (9) is coupled to the testing apparatus (7) with said means (12) for transmitting electrical signals, which testing card (9) is placed in said means (19) for coupling the testing card to the wireless station for carrying out the measurement, that said testing card (9) comprises at least one measuring head (6) and a grounding connection (10), and when the testing card (9) is installed, the measuring head (6) switches said switching means (3, 22) to the second position, the grounding means (10) are coupled to an electrically conductive connection in the grounding connection (13), and the measuring head (6) is coupled to an electrically conductive connection in said switching means (3, 22), whereupon the radio frequency signal is directed between the radio part (8) of the wireless station (1) and the testing apparatus (7) via the measuring head (6) and testing card (9).
18. A method according to ~~any one of the claims 15, 16 or 17~~ claim 15, whereby the wireless station (1) comprises at least one SIM card (18), **characterized** in that the above mentioned means (19) for coupling the testing card to the wireless station comprise at least one SIM card slot (19), in which the SIM card (18) is

placed, whereupon the above mentioned testing card (9) is placed instead of the SIM card (18) in the SIM card slot (19) for carrying out the measurements.